



SAFETY DATA SHEET

1. Identification of the Substance and Company

Steraffirm Bowie Dick Test Pack
Product No. EQC001, EQC002, EQC003
MSDS No. B104

NFPA 704 HAZARD RATING:

HEALTH: 0
FIRE: 0
REACTIVITY: 0

Prepared by: Richard Bancroft
asksteris_msds@steris.com

Date Created: September 9, 2009 Date Revised: N/A Date Reviewed: N/A

STERIS Corporation, P.O. Box 147, St. Louis, Mo 63166, US
Emergency Telephone No. 1-314-535-1395 (STERIS); 1-800-424-9300 (CHEMTREC)
Telephone Number for information: 1-800-444-9009 (Customer Service-Scientific Products)

Albert Browne Limited, Chancery House, 190 Waterside Road, Hamilton Industrial Park,
Leicester, LE5 1QZ, UK

Product/Technical Information Phone No: 44 (0)116 276 8636

Product Number	Cycle Type	Cycle Parameters
EQC001	Prevacuum	132°C/270°F for 3 to 4 minutes
EQC002	Prevacuum	134°C -137°C/273°F - 279°F for up to 3.5 minutes
EQC003	Prevacuum	121°C - 124°C/250°F- 255°F for 8 to 8.3 minutes

Steraffirm Bowie Dick Test Packs are not hazardous products according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200 and the Controlled Products Regulations; and are free of lead and other heavy metals.

Steraffirm Bowie Dick Test Packs do not contain any components derived from animal origin, do not come into contact with materials of animal origin and therefore comply with the "Note for guidance of minimizing the risk of transmitting animal spongiform encephalopathy agents via human Veterinary medicinal products (EMEA/410/01 Rev. 2-October 2003)."

Steraffirm Bowie Dick Test Packs contain natural dry rubber.

The Steraffirm Bowie Dick Test Pack verifies that the prevacuum sterilizer effectively removes air and provides efficient steam penetration. The advanced thermochromic ink formulation can detect problems with steam quality.

Store at 0-30°C in dry (30 – 60% RH) conditions away from direct sunlight.